# Sediment PCB Cleanup Remedy Effectiveness: Case Study Synthesis


Presented by: Clay Patmont, Anchor QEA Collaborators: Paul Doody and Betsy Henry, Anchor QEA Suzanne Replinger, Windward





# >15 million cubic yards dredged >\$10 billion spent (2022 dollars)

# Was PCB sediment remediation successful?





5. Duwamish Wate

6. East Waterway, 7. Elliott Bay, WA

#### Sediment PCB Cleanup Sites 1. Cedar Creek, WI 8. Field Brook/Ashtabula River, OH 15. Mirror Lake, DE 2. Commencemen 3. Columbia Sloug 4. Cumberland Bay

ent Bay, WA	9. Fox River ,WI	16. Onondaga Lake, NY	23. Sangamo Weston/Lake Hartwell, SC
gh, OR	10. Grasse River, NY	17. Ottawa River, OH	24. San Diego Bay, CA
ay, NY	11. Housatonic River, MA	18. Passaic River, NJ	25. Sheboygan River and Harbor, WI
terway, WA	12. Hudson River, NY	19. Pearl Harbor, HI	26. Sinclair Inlet/Bremerton Naval Shipyard, WA
, WA	13. Kalamazoo River, MI	20. Portland Harbor, OR	27. Town Branch Creek/Mud River, KY
	14. Manistique River and Harbor, MI	21. Puget Sound, WA	28. Waukegan Harbor, IL

22. River Raisin, MI

# Sediment Remediation Case Study Reviews

- Retrospective reviews of completed projects with robust monitoring
  - More broadly developed knowledge to inform future sediment cleanup remedies
- June 2019 Anchor QEA Seattle Workshop
  - 12 case study presentations (many Pacific Northwest sites; <u>https://www.smwg.org/</u>)
  - 66 participants (industry and federal, state, and local agencies)
- October 2022 SMWG Detroit Symposium
  - 12 case study and 4 summary presentations (<u>https://www.smwg.org/</u>)
  - 150 participants (industry and federal/state agencies)

# Eight Common Topics for Each Case Study

- 1. Objectives of remediation
- 2. Summary of completed early actions and/or final remedy
- 3. Significant remedy scope or schedule deviations
- 4. When were external sources characterized and addressed?
- 5. Primary pre- and post-remedy effectiveness monitoring elements
- 6. Did the remedy achieve remediation objectives for surface sediment?
- 7. Is the remedy on track to achieve water/biota remediation objectives?
- 8. Key take-home messages on overall lessons learned

## Common Case Study Themes

- Cooperative partnerships are more efficient
- Source control in urban settings is difficult but critical
- Remedy flexibility and adaptive management improve success
- Remediation successfully reduces sediment concentrations
- Mixed remedy success reducing PCB bioaccumulation exposures
  - Robust baseline and >7 years postconstruction monitoring needed for evaluation
  - Only a subset of case studies currently have sufficient robust monitoring data

## $\mathcal{O}$ APPROACH

## Robust PCB Remedy Effectiveness Case Studies


- Fox River, Wisconsin (Tara Van Hoof's presentation earlier in this session)
- Hylebos Waterway, Washington
- Sinclair Inlet, Washington
- San Francisco Bay, California

# Fox River, Wisconsin

- PCBs from carbonless copy paper discharged from 1954 to 1971
- Operable Unit (OU) 1: 2004 to 2009
  - Dredge (370,000 cy), cap, and cover
- OU 2: natural recovery subareas
- OU 3: 2009 to 2011
  - Dredge (240,000 cy), cap, and cover
- OU 4: 2007 to 2020
  - Dredge (5,880,000 cy), cap, and cover



Fox River Remedy Effectiveness: Wet Weight Tissue




Surface Sediment vs. Walleye Fillet Tissue PCB Concentration Changes

Sources: Anchor QEA (2007); Foth (2019); and Tetra Tech, Inc. et al. (2021)

Surface Sediment (0 to 15 cm) Total PCB Aroclor Conc. (mg/kg dry; mean ± std. err.)

## Fox River Remedy Effectiveness: Lipid Normalized



Surface Sediment vs. Walleye Fillet Lipid-Normalized PCB Concentration Changes

Sources: Anchor QEA (2007); Foth (2019); and Tetra Tech, Inc. et al. (2021)

Surface Sediment (0 to 15 cm) Total PCB Aroclor Conc. (mg/kg dry; mean ± std. err.)

### LESSONS

# Fox River PCB Recovery

- Natural recovery and remedial actions (dredging, capping, and cover) all contributed to recovery
  - Similar reductions in surface sediment, fish tissue, and water column PCBs
    - Important covariates (e.g., fish lipid content)
    - Diminishing linkage between surface sediment and fish tissue PCB at lower levels



# Hylebos Waterway, Washington


- Part of Commencement Bay Site
- Numerous historical PCB sources
  - Extensive wastewater/stormwater controls and upland/shoreline cleanup actions: 1985 to 1999
  - Source control verified in 2001
- Sediment remediation: 2001 to 2006
  - 24 acres dredged (1,500,000 cy)
  - 8 acres monitored natural recovery
  - 3 acres capped





## Hylebos Waterway Segment 4 Sediment Monitoring

- 1999 remediation of larger shoreline PCB source
- Offshore surface sediment recovered 5 times faster than simple model projections
  - Dynamic/rapid equilibrium; more flux than net deposition
- Source control most effective reducing sediment PCB levels




#### Surface (0-10 cm) Sediment PCB Aroclors

# Sinclair Inlet, Washington

- Numerous historical shipyard PCB sources
  - Continuous process improvements and upland cleanup actions beginning in 1992
- Navigation dredging in 1994/1995
- Navigation/Superfund actions in 2000/2001
  - 32 acres dredged (225,000 cy)
  - 13 acres capped or sand covered
- Shipyard infrastructure projects in 2011
- Fish tissue sampling: 1991 to 2017







# Sinclair Inlet Remedy Effectiveness Monitoring

- Tissue peaks associated with in-water construction releases
  - Similar data from
     Commencement Bay
- Little net change in tissue PCB levels over 26 years





# Puget Sound Remedy Effectiveness Monitoring



Surface Sediment vs. English Sole Fillet Tissue PCB Concentration Changes


Sources: Tetra Tech (1985), West et al. (2017), EPA (2020), Windward (2020), and Anchor QEA (2022)

Surface Sediment (0 to 10 cm) Total PCB Aroclor Conc. (mg/kg dry; mean ± std. err.)

### LESSONS

# Puget Sound PCB Recovery

- Diminishing linkages between surface sediment and fish tissue at lower PCB levels
  - Non-sediment factors such as water column exposures become predominant
- Source control and natural recovery have generally been more effective than remediation
  - Particularly after higher PCB sediments are addressed
  - Dynamic/rapid equilibrium of surface sediment
  - Unavoidable short-term dredging releases




# San Francisco Bay PCB Exposure Control Strategy

• Reduce stormwater sources in watershed to achieve 0.01-mg/kg fish tissue criterion


Source Category	PCB Loading (kg/yr)	
Stormwater runoff	20	
Central Valley drainage	11	
Municipal dischargers	2.3	
Industrial discharges	0.035	
Navigation dredging	Net Loss	
Sediments	Net Sink	

Source: California Regional Water Quality Control Board (2008)



California Regional Water Quality Control Board San Francisco Bay Region Municipal Regional Stormwater NPDES Permit

> Order No. R2-2015-0049 NPDES Permit No. CAS612008 November 19, 2015



# Summary

- As sediment concentrations decrease, sediment linkages with fish tissue PCB concentrations diminish
  - Non-sediment factors such as water column exposures become predominant
- Source control in urban settings is difficult but critical
  - Source control has generally been more effective than sediment remediation, particularly after higher PCB sediments (hotspots/early actions) are addressed
  - Site-specific dynamic equilibrium of surface sediments with ongoing sources
- Additional case studies with robust baseline and >7 years postconstruction monitoring data pending





# Clay Patmont

Principal Anchor QEA cpatmont@anchorqea.com



#### REFERENCES

Anchor QEA (Anchor QEA, LLC), 2003. *Preliminary (30 Percent) Design Memorandum, Hylebos Waterway Remedial Design, Segments 3 and 4*. Prepared for U.S. Environmental Protection Agency. May 2003.

Anchor QEA, 2007. *Baseline Monitoring Data Report: 2006–2007, Lower Fox River, Wisconsin.* Prepared for U.S. Environmental Protection Agency. July 2009.

Anchor QEA, 2021. *Sediment Data Summary Report, Mouth of Hylebos Waterway (Segments 3, 4, and 5)*. Prepared for U.S. Environmental Protection Agency. November 2021.

Anchor QEA, 2022. *Puget Sound Surface Sediment Data Compilation (2008 to 2021)*. Unpublished mapping update. November 2022.

California Regional Water Quality Control Board, 2008. *Total Maximum Daily Load for PCBs in San Francisco Bay, Final Staff Report for Proposed Basin Plan Amendment*. February 2008.

EPA (U.S. Environmental Protection Agency), 2020. Commencement Bay Data Release for PCB Aroclor Results from the Region 10 USEPA Laboratory. March 2020.

Foth (Foth Infrastructure & Environment, LLC), 2019. *Long-Term Monitoring Summary Report, Lower Fox River Operable Units 1-3*. Prepared for P.H. Glatfelter Company. March 2019.

#### $\mathsf{R}\mathsf{E}\mathsf{F}\mathsf{E}\mathsf{R}\mathsf{E}\mathsf{N}\mathsf{C}\mathsf{E}\mathsf{S}$

Hylebos Cleanup Committee, 1999. Pre-Remedial Design Evaluation Report, Hylebos Waterway, Commencement Bay Nearshore/Tideflats Site. Prepared for U.S. Environmental Protection Agency. November 1999.

Tetra Tech, Inc., 1985. *Commencement Bay Nearshore/Tideflats Remedial Investigation*. Prepared for Washington State Department of Ecology and U.S. Environmental Protection Agency. TC-3752. August 1985. Tetra Tech, Inc., J.F. Brennan, and Stuyvesant Project Realizations, 2022. *OUs 2-5 Remedial Action Certification of Remedial Action Completion Report*. Prepared for Lower Fox River Remediation LLC. July 2022.

West, J.E., S.M. O'Neill, and G.M. Ylitalo, 2017. "Time Trends of Persistent Organic Pollutants in Benthic and Pelagic Indicator Fishes from Puget Sound, Washington, USA." Archives of Environmental Contamination and Toxicology 72(2):207– 229. DOI: 10.1007/s00244-017-0383-z.

Windward, 2020. Lower Duwamish Waterway Pre-Design Studies Data Evaluation Report. June 2020.